



# Drum Scrubber

#### Standard features

	Gasketed lid	HDPE Vessel		
Drain Valve	Weatherproof motor	Coupling connection		
	Anticorrosion hardware			

## **Electrical data**

Voltage	Phases	Frequency		
110-120	1	60		
208-240	1/3	50/60		
380	3	50		
440-460	3	50/60		

## **Recommended Applications**

WWT	PTAR	Pump Stations
Wells	Lift stations	

English units			Metric Units					
CFM	Vol	Dimensi	Dimensions (in)		Vol	Dimensi	Dimensions (cm)	
	ft3	D	Н		m3	D	Н	
100	5	24	48	170	0.14	61	122	
300	10	30	60	510	0.28	76	152	
500	17	36	60	850	0.48	91	152	
750	27	45	48	1,275	0.76	115	122	
1,000	39	52	60	1,700	1.10	132	152	

### **VEL DS**

The DS is engineered to eliminate odorous gases in various environments. including wastewater treatment facilities, pump stations, lift stations, wet wells, force mains, and wastewater treatment plants. Constructed from corrosion-resistant materials and designed for minimal maintenance, the DS is suitable for use in remote outdoor areas or zones with high levels of acid gases. This scrubber features layered beds of chemical media and can be customized with optional add-ons such as passive configurations, silencers, mist/grease eliminators, and rain hoods













